



Fan-free POS Terminals that run cool even with high quality 8" TFT LCD panel



Optional built in magnetic stripe reader (MSR).



CF card slot for optional CF memory card which allows booting from HDD or optional CFcard.

The Posiflex DT-208 is a mini sized, fully functional, quiet FanFree POS systems, suitable for all types of applications including retail and hospitality. Although small the DT series are perfectly formed, with the efficiency of a much larger system and the DT series boasts 4 serial ports, 3 USB, 1 LAN, 1 cash drawer port and supports 2.5" 40GB HDD or CF card. With the built-in programmable keyboard and touch or non-touch screen the DT series saves even more space. Built with the metal + plastic housing heat is evenly dissipated to allow the DT series to be utilized in everyday and harsh environments and the built-in UPS functionality ensures your system keep running when others fail.

The DT series offers all these features at an affordable price, with a choice of Windows or DOS support, to make your life easier with a Posiflex system.

- CPU: AMD LX700.
- Support Microsoft WEPOS, POS Ready, WinCE and DOS environment.
- Compact and rugged metal housing including a storage room for HDD and WiFi module.
- 4 COM ports with DC power support for peripheral devices in any industrial application.
- Optional HDD, WiFi module with external antenna.
- Various I/O ports supported.
- DDR SDRAM memory can extend to 1 GB in 1 DDR SO-DIMM module.
- VGA memory size program by software 16 up to 254 MB.
- Built-in UPS function to support the system from intermittent power failure (battery itself is an option).
- Supports power saving mode.



Fan-free



CPU



WiFi



UPS

Posiflex Fan-Free POS Terminal DT-208/208H



Function	DT-208	DT-208 H
CPU	AMD LX-700	
System Memory	DDR SODIMM socket*1, Max 1G.	
Default Memory Size	256 MB	
Power Supply	12 VDC power adaptor	
Housing	Metal + Plastic Housing	
Programmable KB	40 Keys, Stroke Type	
OS support	WinCE / WEPOS / POS Ready / Linux / DOS	
EMI / Safty Certifications	<ul style="list-style-type: none"> · Whole system is CE, FCC class A approved · Power supply is UL, TUV approved · RoHS · WEEE 	
Dimensions	224 mm (W) x 307~312 mm (D) x 108~256 mm(H) or 8.8" x 12.1"~12.3" x 4.3"~10.1"	
Weight	3.3 kg (7.3 lbs)	
Display		
LCD	8" LCD panel 800x600	
Touch Controller	N/A	PS/2
Touch Sensor	N/A	5 Wire Touch Panel
Tilt Adjustment	15°~90°	
Expansion		
Storage Device	2.5" 40 GB IDE HDD or CF memory card (Option)	
CF card slot	Y (memory card only)	
LAN Port	10 / 100 Mb	
Serial Port	4 x DB9	
UPS Port	Y	
Standard USB Port	3 x	
CR Port	1 x	
Power ON only control	Y	
Extension Slot	Y (Mini PCI Slot for Wi-Fi module)	
Environment		
Operation Condition	0°C ~ +40°C or 32°F~ +104°F	
Storage Condition	-20°C ~ +60°C or -4°F~ +140°F	
Options		
Customer Pole Display	PD-201(1x16 LCDM, RS-232 Only) PD-309(2x20 LCDM, 200mm pole) PD-2605(2x20 VFD, 200mm pole)	
UPS Battery	2.3 AH / 12V Lead Acid battery	
CF Memory Card	Optional	
MSR	Optional	
WiFi	Optional	

** The product information and specifications are subject to change without prior notice.

2009 V.02



Optional WLAN module supports IEEE 802.11 a/b/g and WinCE driver.



Optional customer display for integrated base mounted device PD309/U (2 x 20) LCD pole display.



Optional rear mounted device PD-201 LCD customer display.



Posiflex Technologies, Inc.
6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan, R.O.C.
Tel: 886 2 2299-1599 Fax: 886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

