

KS-6200 Series 6215N / 6215N-Plus **Fan-free**



Wall-Mount



Side mount attachment integrates, optional MSR and optical finger print sensor



36 key plus lock keypad and/or MSR and/or Smart card reader



Real mount customer pole display



Customer Display Module
Optional 12.1" / 15" LCD display unit mounts on rear bracket of ks stand

Features

- Low power consumption and fanfree design for quiet operation
- Effective heat dissipation design of aluminum die casting main housing
- Durable resistive type touch sensor
- A patented finger release lever "Gear Lock" mechanism easily adjusts the LCD tilt angle from 15° to 70°
- High serviceability mechanical design for easy HDD maintenance and memory upgradeability
- Push-open cover to protect power switch from accidental shutdown of the system, providing extra security to the operation
- Choice of rear mount option between customer pole display and 2nd LCD display

Specification	KS-6215N	KS-6215N- Plus
Processor	VIA C7 1.5GHz	
Memory	DDR2 , 512MB, SO-DIMM x 1, max. 1 GB	
VGA Memory	Default 16 MB, expandable to 64 MB shared memory from system memory	
Power Supply	+12 V DC power adaptor, 80 W	
Housing	Aluminum die casting	
Front bezel	Textured	
Base Stand	Gen 4 base or Gen 5 base or wall-mount	
Speaker	Built-in	
OS support	WinCE, WinXP pro, WEPOS, POSReady, Linux.	
Compliance	FCC-A, CE-A, RoHS, WEEE	
Display		
LCD	15" LCD, 1024x768	
Touch Sensor	5 wires resistive	
Touch Controller	USB interface	
Brightness Control	Hardware VR control or software control	N/A
Tilt Adjustment	From 15° to 70°	
Expansion		
Storage Device	2.5" 80GB HDD	2.5" 80GB SATA HDD or optional CF memory card
Connectivity		
Audio Port	Built-in: 2 W audio amplifier with internal speaker Mic. in / line out ports in SD-400 option	
LAN Port	10 / 100 Mb	
Parallel Port	Yes	
Serial Port	x 4, with + 5 V power supply capability in 10 pin modular connector	x 2, with + 5 V / + 12 V power supply capability
UPS Port	Yes	N/A
Standard USB Port	x 4	
Proprietary USB Port	1 for right side mount option	
VGA Port	D-Sub 15 pin	
CR Port	N/A	Yes, one port control one Cash Drawer
PS2 / KB Port	1	N/A
Physical Dimension		
Dimension (W x D x H in mm)	LCD@15°:378x304x364mm(12.5"x12.0"x14.3") LCD@70°:378x304x274mm(12.5"x12.0"x10.8")	LCD@15°:378x308x359mm (14.9"x12.1"x14.1") LCD@70°:378x297x283mm (14.9"x11.7"x11.1")
Weight (N. W. in kg)	9.3	9.1
Environment		
Operation Condition	0°C~+35°C (32°F~+95°F), 20%RH~80%RH, non-condensing max. wet bulb 26°C (78.8°F)	
Storage Condition	-20°C~+60°C (-4°F~+140°F) , 10%RH~80%RH, non-condensing max. wet bulb 28.9°C (84.0°F)	
Options		
2nd HDD	Yes	
2nd LCD Display	12" LM-6101; 15" LM-6501, VGA port	
Customer Pole Display	PD-2602: Base mount 9 mm VFD pole display, 5 x 7 matrix, USB or RS232 interface PD-306: Base mount 9 mm LCD pole display, 5 x 7 matrix, RS232 or USB interface	
MSR	SD-400 / SD-400Z: MSR and/or Finger print sensor SD-800: MSR (1/2/3) and/or RFID (option) and/or WIFI (option)	
KP-300W	Mic In and Line out and 36 key plus lock keypad and/or MSR and/or Smart card reader	
UPS Battery	2.3 AHr / 12 V in base	N/A
Wireless LAN	IEEE 802.11 a/b/g/n, USB interface, external Dongle type	

❖ The product information and specifications are subject to change without prior notice.

2010 V.02

Posiflex Technology, Inc.

6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan
Tel: 886 2 2299-1599 Fax: 886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

